

# **PARTNER**

CARE . TRUST . RESPONSIBILITY

PT-6200 & PT-6212

## PT-6200 and PT-6212 fanless All in One POS Terminals



The All in One POS Touch Terminals PT-6200 and PT-6212 are the solutions for small and medium size enterprises. They can help to serve customers

effectively, and keep pace with competitors.

The compact base embedded with 80mm thermal printer, touch screen and integrated customer display, design with attractive appearance and small footprint for counter space saving, PT-6200 and PT-6212 can fit in with any environment installation.

They can be used as well as in retail, kiosk, fashion or in hospitality.

### **Special Features:**

- Fanless
- Touch Screen 10.4" or 12.1"
- Integrated thermal printer 80 mm
- Card Reader Track 1, 2, 3
- External power supply
- Options: RFID, Raid, SSD

## All in One POS Terminals PT-6200 and PT-6212 fanless



### Technical data

	PT-6200	PT-6212
LCD	10.4" TFT-LCD, resolution is 800 x 600	12.1" TFT-LCD, resolution is 1024 x 768
Touch	5-wire Resistive touch (PS/2 interface)	5-wire Resistive touch (PS/2 interface)
CPU	Intel Celeron-M Processor @ 600MHz, FSB 400MHz, fanless design	Intel Celeron-M Processor @ 1GHz, FSB 400MHz, fanless design
Chipset	NB-Intel 82852GM; SB-Intel 82801DB	NB-Intel 910GML; SB-Intel ICH6-M
Memory	184-pin DDR DIMM x 1, System chip with 512MB as the standard	200-pin DDR2 SO-DIMM x 2, System chips with 1G as the standard
Graphics	Intel®852GM(E) integrated dynamic video shared memory On board LVDS connector for LCD support	Intel® Graphics Media Accelerator 900 (Intel® GMA 900) On board LVDS connector for LCD support
Ethernet	Realtek Giga LAN	Realtek Giga LAN
Audio	Realtek Two-channel AC'97 2.3 Audio Codec	VIA Two-channel AC'97 2.3 Audio Codec
HDD	Internal 3.5" type IDE HDD 80GB or above	Internal 3.5" type SATA HDD 80GB or above
I/O Interface	4 x COM ports 1 x RJ11 port for cash drawer(+24V) 1 x PS2 Keyboard port, auto routing for MSR, no jumper 1 x RJ-45 LAN port with activity and link LEDs 4 x USB ports 1 x DC + 12V power adaptor connector	4 x COM ports 1 x VGA port 1 x RJ11 port for cash drawer(+24V) 1 x PS2 Keyboard port, auto routing for MSR, no jumper 1 x RJ-45 LAN port with activity and link LEDs 4 x USB ports 1 x DC + 12V power adaptor connector
Dual Display	none	available
Peripherals (built in)	Tripple-track MSR (PS/2 interface) Customer display module (serial interface) 3" Thermal receipt printer with cutter + control board (serial interface)	Tripple-track MSR (PS/2 interface) Customer display module (serial interface) 3" Thermal receipt printer with cutter + control board (serial interface), built in
Operations System	WEPOS/Windows 2000/CE. Net/Linux Pos Ready, Windows XP	POSReady 2009/WEPOS/Windows 2000/CE. Net/Linux Windows 7, Windows XP
Dimension	Physical: 328 mm (W) x 289.3 mm (D) x 246.8 mm (H)	Physical: 328 mm (W) x 295.3 mm (D) x 246.8 mm (H)
Colours	black, white	black, white
Options	Solid State Drive, RFID Reader, Raid, WLAN	Solid State Drive, RFID Reader, Raid, WLAN