

PARTNER

CARE . TRUST . RESPONSIBILITY

PT-6910 / PT-6915

POS Terminals PT-6910 / PT-6915 The fanless POS Solution



The PT-6910 and PT-6915 are not only elegantly designed - these high-end products are also equipped with a high-performance Celeron M CPU that guarantees particularly efficient and powerful processing, a 15" TFT touch screen monitor and low energy consumption, which contributes noticeably to the reduction of long-term costs.

The compact form and dimensions of the PT-6910 and PT-6915 are ideal when space is limited. Another factor contributing to its extreme reliability and absolute minimum maintenance requirements is that these products can have no moving parts.

The adjustable 15" TFT touch screen monitor can be adjusted to suit the needs of any workplace. Various optional peripherals allow the PT-6910 and PT-6915 to be individually matched to any working situation.

Special Features:

- Celeron M CPU
- 5-wire resistive touch screen
- Fanless
- Low energy consumption
- Adjustable monitor
- External power supply

Optional:

- 2 x 20 alphanumeric display,
- I-Button, KB-32 keyboard
- Fingerprint, Card Reader,
- RFID, 2nd LCD 15" Display
- Dallas Lock, Addimat Lock,
- capacitive touch screen

The fanless POS Solution PT-6910 / PT-6915



Technical data

	PT-6910	PT-6915	PT-6915 F
CPU	Intel® Celeron-M 1.0GHz, FSB 400 MHz, Fanless	Intel® Celeron-M 1.5GHz, FSB 400 MHz, L2 cache 1 M, Fanless	Intel® Celeron-M 1.5 GHz, FSB 400 MHz, L2 cache 1 M
NB	Intel® QC82910GML E	Intel® QC82910GML E	Intel® QC82910GML E
SB	Intel® NH82801FBM	Intel® NH82801FBM	Intel® NH82801FBM
Memory	DDR 2 400/533MHz 200 Pin SO DIMM x 1, max. 2 GB	DDR 2 400/533 MHz 200 Pin SO DIMM x 1, max. 2 GB	DDR_2 400/533 MHz 200 Pin SO DIMM x 1, max. 2 GB
HDD	3.5" SATA HDD	3.5" SATA HDD	3.5" SATA HDD
CF	1 (Cable + Module, IDE)	1 (Cable + Module, IDE)	1 (Cable + Module, IDE)
USB Port	8 (2 reserved for DOC)	8 (2 reserved for DOC)	8 (2 reserved for DOC)
Com Port / Power com (5V/12V)	6/4	6/4	6/4
Touch controller	eGalax (COM5, DC + 5 V)	eGalax (COM5, DC + 5 V)	eGalax (COM5, DC + 5 V)
Cash drawer	One RJ-11 Cash drawer port support DC + 24 V, & 2 cash drawer kick out/status	One RJ-11 Cash drawer port support DC + 24 V, & 2 cash drawer kick out/status	One RJ-11 Cash drawer port support DC + 24 V, & 2 cash drawer kick out/status
Printer Port	1 x parallel	1 x parallel	1 x parallel
LAN	10/100M/1G (RTL8110)	10/100M/1G (RTL8110)	10/100M/1G (RTL8110)
Audio/MIC Port	Available	Available	Available
Power Type	Adapter 19V (4.75A) (3P)	Adapter 19V (4.75A) (3P)	Adapter 19V (4.75A) (3P)
VGA Port	D-15 sub	D-15 sub	D-15 sub
Dual Display	Available	Available	Available
BIOS	Award 4 M (LPC)	Award 4 M (LPC)	Award 4 M (LPC)
LCD Panel	AUO-G150XG03 (Replaceable lamp)	AUO-G150XG03 (Replaceable lamp)	AUO-G150XG03 (Replaceable lamp)
Touch Panel	5-wire resistive or capacitive	5-wire resistive or capacitive	5-wire resistive or capacitive
O/S Support	Windows 7, Windows 2000/XP/XPe, Wepos, POSReady, Linux	Windows 7, Windows 2000/XP/XPe, Wepos, POSReady, Linux	Windows 7, Windows 2000/XP/XPe, Wepos, POSReady, Linux
Options	MSR (PS/2), Rear Display, 2nd LCD, 15" Display, Fingerprint, I-Button, KB-32 Keyboard, RFID, Dallas Lock, Addimat Lock, Solid State Drive, capacitive touch screen	MSR (PS/2), Rear Display, 2nd LCD, 15" Display, Fingerprint, I-Button, KB-32 Keyboard, RFID, Dallas Lock, Addimat Lock, Solid State Drive, capacitive touch screen	MSR (PS/2), Rear Display, 2nd LCD, 15" Display, Fingerprint, I-Button, KB-32 Keyboard, RFID, Dallas Lock, Addimat Lock, Solid State Drive, capacitive touch screen