

PARTNER

CARE . TRUST . RESPONSIBILITY

RP-300H

High-Speed POS Printer



The RP-300H is an extremely fast and powerful thermalbond printer with up to 200 mm/s printing speed and a resolution of 180 dpi.

With its compact size and integrated wall-mounting feature this durable model is perfect for use in various applications areas.

A variety of interface possibilities allow for the easy connection of the printer to an existing cash register system.

Due to the singular one-of-a-kind technology the RP-300H with 8 MB of logo memory can print simultaneously coupons, promotional texts, rebate offers or other customer information.

Special Features:

Resolution 180 dpi

8 MB logo memory

Interface Options:
RS232,USB,parallel, LAN,
WLAN

Integrated Wall mounting

Signal tone remote

Autocutter

Power Supply included

Available in black and light
grey

High Speed POS Printer RP-300H



Technical data

Printing method	Direct Thermal	
Printing speed	200 mm/sec	
Dot density	180 dpi	
Dot pitch	0.141 mm	
Effective printing	Width: 72 mm, 512 dots/line	
Character per line	Font A: 42 columns; Font 56 columns; Big5, GB Kanji: 21 columns	
Paper	Type: Thermal paper Width: 80 mm (+- 0.1) Thickness: 0.06~0.09 mm Roll diameter: Max. 83.0 mm Roll core inner diameter: 12.5 mm +- 0.5 mm	
Interface	Serial (RS-232C), Parallel (IEEE-1284), USB, Ethernet, WLAN	
Power Adapter	AC 100V~240V, 50~60 HZ	
Dimension	152 mm (W) x 194 mm (D) x 148 mm (H)	
Environment	Operating	Storage
	Temperature: 5~40° C	-20~60° C
	Humidity: 35%~80%	10%~90%
Auto cutter	Type: Guillotine Paper Thickness: 0.06~0.09 mm Cutting method: full/partial cut	
Color	light grey and black	
Options	Spill Prove Cover, Black mark sensor	

